

Admin Functions	Command Line
COPY .. FROM .. COPY .. TO .. current_setting pg_cancel_backend pg_column_size pg_database_size pg_relation_size pg_size_pretty pg_tablespace_size pg_total_relation_size set_config vacuum analyze verbose vacuum full	pg_dump pg_dumpall pg_restore psql
Common Functions	SQL Keywords
cast, :: coalesce generate_series greatest least nullif random	BETWEEN .. AND CASE WHEN .. END DELETE FROM DISTINCT DISTINCT ON EXISTS FROM GROUP BY HAVING LIKE IN(..) LIMIT .. OFFSET NOT NOT IN(..) NULLS FIRST ¹ NULLS LAST ¹ ORDER BY SELECT SET SIMILAR TO TRUNCATE TABLE UPDATE USING WHERE
Sequence (Serial) Functions	Aggregates
curval lastval nextval	avg bit_and bit_or boolean_and boolean_or count count(DISTINCT) every max min stddev sum sum(DISTINCT) variance xml_agg ¹
String Functions	DDL
 ascii chr initcap length lower lpad ltrim md5 position quote_ident quote_literal regexp_matches regexp_replace regexp_split_to_array regexp_split_to_table repeat replace rpad trim split_part strpos substr trim upper	ADD CONSTRAINT CREATE AGGREGATE CREATE CAST CREATE (DEFAULT) CONVERSION CREATE DATABASE CREATE DOMAIN CREATE [OR REPLACE] FUNCTION CREATE (UNIQUE) INDEX CREATE LANGUAGE CREATE OPERATOR CREATE OPERATOR FAMILY ¹ CREATE ROLE CREATE RULE CREATE SCHEMA CREATE SEQUENCE CREATE TABLE CREATE TABLESPACE ALTER TABLE CREATE TYPE CREATE [OR REPLACE] VIEW DROP [object]
Database Globals	Enums ¹
current_date current_time current_timestamp current_user localtime	> < <= >= enum_cmp enum_first enum_larger enum_last enum_range enum_smaller
Date Functions	XML ¹
age date_part(text, timestamp) century day decade dow doy epoch hour month quarter second week year date_trunc extract interval to_char to_date to_timestamp	database_to_xml database_to_xmlschema query_to_xml query_to_xml_and_xmlschema table_to_xml xmlattributes xmlcomment xmlconcat xmlelement xmlforest xpath xmlpi xmlroot
Date Predicates	Math Operators
overlaps	%, ^, / /, !/ #, &, #, <, << >>
Array Constructs	Math Functions
ANY(array) ARRAY{4,5,6},... ARRAY() array_append array_cat array_dims array_lower array_prepend array_to_string array_upper SOME(array) string_to_array	This is a subset abs cbt ceiling degrees exp floor log ln mod pi power radians random sgt trunc
Array Operators	Key Information Schema Views
= << < > >> 	columns sequences tables views
Math Operators	Key pg_catalog Tables/Views
+, -, *, / /, !/ #, &, #, <, << >>	pg_class pg_rules pg_settings pg_stat_activity pg_stat_database pg_tablespace
Trig Functions	Large Object
acos asin atan atan2 cos cot sin tan	Server Client lo_creat lo_close lo_create lo_create lo_export lo_create lo_import lo_export lo_unlink lo_import lo_seek lo_open lo_read lo_read lo_tell lo_unlink lo_write

Official PostgreSQL 8.3 Documentation URL: <http://www.postgresql.org/docs/8.3/static/>
 We cover only a subset of what we feel are the most useful constructs that we could squash in a single cheatsheet page

commonly used
¹ New in this release.

DATA TYPES

Below are common data types with common alternative names.
 Note: There are many more and one can define new types with create type. All table structures create an implicit type struct as well.

datatype[] - e.g. varchar(50)[] (defines an array of a type)

- bit
- boolean
- bytea
- character varying(length) - varchar(length)
- character(length) - char(length)
- date
- enum 1
- double precision - float4 float8
- integer - int4
- bigint - int8
- numeric(length,precision)
- oid
- serial - serial4
- bigserial - serial8
- text
- time without timezone - time
- time with timezone - timest
- timestamp without timezone - timestamp
- timestamp with timezone - timestamptz
- xml 1

ADMIN EXAMPLES

```
select pg_size_pretty(pg_tablespace_size('pg_default')) as tssize,
       pg_size_pretty(pg_database_size('somedb')) as dbsize,
       pg_size_pretty(pg_relation_size('someschema.sometable')) as tblsize;
```

--Example importing data to table sometable
 --from tab delimited where NULLs appear as NULL
 COPY sometable FROM "/path/to/textfile.txt" USING DELIMITERS '\t' WITH NULL As 'NULL';

--Example exporting a query to a comma separated (CSV) called textfile.csv
 --setting NULLs to text NULL
 COPY (SELECT * FROM sometable WHERE somevalue LIKE '%') TO '/path/to/textfile.csv'
 WITH NULL As 'NULL' CSV HEADER QUOTE AS '';

```
vacuum analyze verbose;  
vacuum sometable;  
vacuum full;
```

--Kills all active queries in selected db and list out process id
 --and username of process and if kill successful
 SELECT procpid, username, pg_cancel_backend(procpid)
 FROM pg_stat_activity
 WHERE datname = 'somedb';

JOIN EXAMPLES

```
SELECT o.order_id, o.order_date, o.approved_date,
       COUNT(i.item_id) As nlineitems,
       SUM(i.unit_price*i.num_units) As total
FROM orders o
INNER JOIN orderitems i ON o.order_id = i.order_id
GROUP BY o.order_id, o.order_date, o.approved_date
HAVING SUM(i.unit_price*i.num_units) > 200
ORDER BY o.approved_date NULLS FIRST;
```

```
SELECT 'x' As bucket, o.order_id, o.order_date,
       COUNT(i.item_id) As nlineitems,
       SUM(i.unit_price*i.num_units) As total
FROM xorders o
INNER JOIN xorderitems i ON o.order_id = i.order_id
GROUP BY o.order_id, o.order_date
UNION ALL
SELECT 'y' as bucket, o.order_id, o.order_date,
       COUNT(i.item_id) As nlineitems,
       SUM(i.unit_price*i.num_units) As total
FROM yorders o
INNER JOIN yorderitems i ON o.order_id = i.order_id
GROUP BY o.order_id, o.order_date
ORDER BY 1,3,2;
```

DDL EXAMPLES

```
CREATE DATABASE somedb
WITH OWNER = somelogin
ENCODING = 'WIN1252';
```

```
CREATE TYPE rating AS
ENUM('none', 'bronze', 'silver',
     'gold', 'platinum');
```

```
CREATE AGGREGATE sum(text) (
SFUNC=textcat,
STYPE=text
);
```

```
CREATE OR REPLACE FUNCTION cp_test(somearg integer)
RETURNS SETOF sometable AS
$$SELECT * FROM sometable where msg_id = $1:$2
LANGUAGE 'sql' STABLE;
```

```
CREATE TABLE orders(
order_id serial NOT NULL,
order_adddeddt timestamp without time zone,
order_rating rating,
CONSTRAINT pk_orders_order_id PRIMARY KEY (order_id)
)
WITH (OIDS=FALSE);
```

UPDATE/INSERT/DELETE EXAMPLES

```
UPDATE sometable
SET somevalue = 5
WHERE sometable.somefieldname = 'stuff';
```

```
INSERT INTO orders(order_adddeddt, order_rating)
VALUES ('2007-10-01 20:40', 'gold'),
('2007-09-01 11:00 AM', 'silver'),
('2007-09-02 10:00 PM', 'none'),
('2007-10-10 PM', 'bronze');
```

```
DELETE FROM sometable
WHERE somevalue = 'something';
```

```
UPDATE sometable
SET calccount = s.theccount
FROM (SELECT COUNT(someothertable.someid) as theccount,
someothertable.someid
FROM someothertable
GROUP BY someothertable.someid) s
WHERE sometable.someid = s.someid;
```

```
INSERT INTO orders(order_adddeddt, order_rating)
VALUES ('2007-10-01 20:40', 'gold');
```

--This is a fast delete that deletes everything in a table so be cautious.
 --Also only works on tables not referenced in foreign key constraints
 TRUNCATE TABLE sometable;

MISCELLANEOUS EXAMPLES

```
--Enum range query using enum defined above - returns all orders in (bronze, silver, gold)
--Sorts in order bronze, silver, gold. Keep in mind if you reverse gold and bronze you get nothing
SELECT *
FROM orders
WHERE order_rating
BETWEEN 'bronze' AND 'gold'
ORDER BY order_rating;
```

```
SELECT monthperiod.*,
array_to_string(ARRAY(SELECT (d + 1)::varchar(20)
FROM generate_series(0,30) d
WHERE monthperiod.start_date + (d || ' day')::interval
BETWEEN monthperiod.start_date
AND
monthperiod.end_date), ',') as thedays
FROM (SELECT (n + 1) As mnum,
trim(to_char(date '2007-01-01' + (n || ' month')::interval, 'Mon')) As short_mname,
trim(to_char(date '2007-01-01' + (n || ' month')::interval, 'Month')) As long_mname,
date '2007-01-01' + (n || ' month')::interval As start_date,
date '2007-01-01' + ((n + 1) || ' month')::interval + - '1 day'::interval As end_date
FROM generate_series(0,11) n) As monthperiod;
```

```
EXPLAIN ANALYZE SELECT * FROM sometable;
```

COMMAND LINE EXAMPLES

These are located in bin folder of PostgreSQL
 To get more info about each do a -help e.g. psql -help

```
pg_dump -i -h someserver -p 5432 -U someuser -F c -b -v -f "\somepath\somedb.backup" somedb
pg_dumpall -i -h someserver -p 5432 -U someuser -c -o -f "\somepath\alldbs.sql"
pg_restore -i -h someserver -p 5432 -U someuser -d somedb -l "\somepath\somedb.backup"
psql -h someserver -p 5432 -U someuser -d somedb -f "\somepath\somefiletoexec.sql"
psql -h someserver -p 5432 -U someuser -d somedb -c "CREATE TABLE sometable(st_id serial, st_name varchar(25))"
-P ' ' only output rows
psql -h someserver -p 5432 -U someuser -d somedb -P "t" -c "SELECT query_to_xml('select * from sometable', false, false, 'sometable')" -o "outputfile.xml";
```